

Technical data

HD 14i VV



Tandem rollers Series HD CompactLine

Tandem roller with two vibrating roller drums

H285

HIGHLIGHTS

- > Excellent view of drum edge, machine and construction site environment
- > Ergonomic driver platform
- > Simple transport, simple loading
- > Simple, intuitive and language-neutral control
- > Compact dimensions

TECHNICAL DATA HD 14i VV (H285)

Weights

Operating weight with cab	kg lbs	4685 10,330
Operating weight with ROPS	kg lbs	4435 9,779
Empty weight without cab, without ROPS	kg lbs	4115 9,074
Max. operating weight	kg lbs	5630 12,414
Axle load, front/rear	kg lbs	2255/2180 4,972/4,807
Static linear load, front/rear	kg/cm lbs/in	16,3/15,8 91.3/88.5
French classification, value/class		10,6/VT0

Machine dimensions

Total length	mm in	2965 116.7
Total height with cab	mm in	2720 107.1
Total height with ROPS	mm in	2590 102.0
Height loading, min.	mm in	1820 71.7
Total length with cab	mm in	2977 117.2
Center distance	mm in	1950 76.8
Center distance with cab	mm in	1960 77.2
Total width	mm in	1506 59.3
Maximum working width	mm in	1430 56.3
Ground clearance, center	mm in	305 12.0
Curb clearance, left/right	mm in	720/720 28.3/28.3
Turning radius, inside	mm in	2650 104.3

Drum dimensions

Drum width, front/rear	mm in	1380/1380 54.3/54.3
Drum diameter, front/rear	mm in	898/898 35.4/35.4
Drum thickness, front/rear	mm in	16/16 0.6/0.6
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	0/50 0.0/2.0

Diesel engine

Manufacturer		Kubota
Model		V2403-CR
Cylinders, quantity		4

Diesel engine

Power ISO 14396, kW/PS/rpm		37.4/50,9/2700
Power SAE J1349, kW/HP/rpm		37,4/50,1/2700
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF

Travel drive

Speed, infinitely variable	km/h mph	0 - 11,0 0.0 - 6.8
Gradeability, with/without vibration	%	30/40

Vibration

Vibration frequency, front, I/II	Hz vpm	60/51 3,600/3,060
Vibration frequency, rear, I/II	Hz vpm	60/51 3,600/3,060
Amplitude, front, I/II	mm in	0,51/0,31 .020/.012
Amplitude, rear, I/II	mm in	0,51/0,31 .020/.012
Centrifugal force, front, I/II	kN lbs	64/39 14,400/8,775
Centrifugal force, rear, I/II	kN lbs	64/39 14,400/8,775

Steering

Swing angle +/-	°	8
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	73 19.3
Water tank, capacity	L Gal	285 75.3

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

EQUIPMENT

Plastic scraper, foldable | ROPS cabin with heating | ROPS, foldable | Safety belt monitoring device | Radio | Protective roof | Edge pressing and cutting equipment | Chip spreader | Compaction meter HCQ | HAMM Temperature Meter (HTM) | Back-up alarm | Telematics system, interface | Working light | Rotating beacon | Battery isolating switch | Bonnet with sound insulation | Additional mirror | Tool kit | Drum edge lighting CompactLine front towing eye

OPTIONAL EQUIPMENT